



EURO-Profile couplings

Safety coupling, Low connection force

The couplings of JWL are robust and impact-resistant and easily connected with one hand. The couplings of series 570 have a user-friendly valve system that reduces the connection force by 50% compared to conventional valve systems currently available. The couplings are safety couplings as they are produced with a two-step release system.

Standard: EURO

Flowdiameter: 7,8 mm

Flow (7 bar, dP 0,5 bar): 1600 l/min


Connectable with the following:

Cejn 320, Hansen Auto Flo 24, Proquix 1420 & 1421, Legris 94xx A, Oetiker SC Series C, Prevost ESC 07/ERC 07, Rectus-Tema 25, 26 & 1600.


Produced with the following connections:





Internal thread, external thread, hose connection and PUR connection.

Dimensions: Series 570



Flowdiagram: Series 570



Thread	Series 570	Art. no.	Thread	Series 570	Art. no.	Specifications
	1/4" BSP int. thread	570-002000		1/4" BSPT ext. thread	570-012000	Housing Steel, el. galvanized
	1/4" NPT int. thread	570-032000		1/4" NPT ext. thread	570-042000	Ball Cage Brass, nickel plated
	3/8" BSP int. thread	570-004000		3/8" BSPT ext. thread	570-014000	Valve Brass
	3/8" NPT int. thread	570-034000		3/8" NPT ext. thread	570-044000	Retain. ring Hardened steel, el. galv
	1/2" BSP int. thread	570-005000		1/2" BSPT ext. thread	570-015000	Guard ring PA6
	1/2" NPT int. thread	570-035000		1/2" NPT ext. thread	570-045000	Balls Hardened steel
	1/4" (6mm) hose con.	570-022000		PUR con ø5/8mm	570-052000	Seals Nitrile rubber
	5/16" (8mm) hose con.	570-023000		PUR con ø6,5/10mm	570-054000	Springs Stainless spring wire
	3/8" (10mm) hose con.	570-024000		PUR con ø8/12mm	570-055000	Max 16 bar
	1/2" (13mm) hose con.	570-025000		PUR con ø9,5/13,5mm	570-056000	150 bar
						-20°C til +60°C

The JWL couplings with external thread can also be delivered with teflon



Made in Denmark
www.jwl.dk