

VALVOLE AD AZIONAMENTO ELETTROPNEUMATICO

SOLENOID PILOT VALVE
ELEKTROPNEUMATISCHE VENTILE
DISTRIBUTEURS ÉLECTROPNEUMATIQUES
VÁLVULAS DE ACCIONAMIENTO ELECTRONEUMÁTICO
VÁLVULAS DE ACIONAMENTO ELETRO-PNEUMÁTICO



CARATTERISTICHE TECNICHE

TECHNICAL CHARACTERISTICS
TECHNISCHE ANGABEN
CARACTÉRISTIQUES TECHNIQUES
CARACTERÍSTICAS TÉCNICAS
CARACTERÍSTICAS TÉCNICAS



Norma di Riferimento

Reference standard

Entspricht der Norm

Norme de référence

Normativa de referencia

Norma de referência

1907/2006



2011/65/CE



ATEX

2014/34/UE

PED

2014/68/UE



		1/8	1/4	1/2
	ATTACCO FILETTATO ROSCA ANSCHLUSS CONNEXION ROSCA CONEXÃO ROSCADA	1/8	1/4	1/2
	PORTATA a 6 BAR con Δp 1 bar 6 bar FLOW RATE with Δp 1 bar DURCHFLOßWERT BEI 6 bar mit Δp 1 bar DÉBIT DE REFERENCE a 6 bar avec Δp 1 bar CAUDAL a 6 BAR con Δp 1 bar VAZÃO a 6 BAR com Δp 1 bar	740 NI/min	1200 NI/min	5000 NI/min
	PRESSIONE DI FUNZIONAMENTO OPERATING PRESSURE BETRIEBSDRUCK PRESSION DE SERVICE PRESIÓN DE EJERCICIO PRESSÃO DE OPERAÇÃO	Monostable	2 ÷ 10 bar	
		Bistable	1 ÷ 10 bar	
	TEMPERATURA TEMPERATURE BETRIEBSTEMPERAUTUR TEMPÉRATURE DE TRAVAIL TEMPERATURA TEMPERATURA	min	-10 °C	
		max	+60 °C	
	TENSIONE SOLENOIDE SOLENOID VOLTAGE SPANNUNG DER MAGNETSPULEN TENSION DE LA BOBINE TENSIÓN SOLENOIDE TENSÃO DA SOLENOIDE	24V DC - 12V DC - 24V AC - 110V AC - 220V AC		
	POTENZA MINIMA MINIMUM POWER MIN. LEISTUNG PUISSANCE MIN. POTÊNCIA MÍNIMA POTÊNCIA MÍNIMA	2W - 3VA		
	COMANDO MANUALE MANUAL CONTROL MANUELLE BETÄTIGUNG COMMANDE MANUELLE COMANDO MANUAL ACIONAMENTO MANUAL	BISTABILE BISTABLE BISTABIL BISTABLE BIESTABLE BIESTÁVEL		
	COPPIA DI SERRAGGIO DELLA GHIERA SUL SOLENOIDE TORQUE OF TIGHTENING THE NUT SOLENOID ANZUGSDREHMOMENT DER SPULENBEFESTIGUNGSMUTTER COUPLE DE SERRAGE DES VIS DE FIXATION DES BOBINES PAR DE APRIETE TUERCA SOBRE LA BOBINA TORQUE DE APERTO DA PORCA DA SOLENOÍDE	0.6 Nm		

Materiali e Componenti

IT

- 1 Corpo in alluminio anodizzato e verniciato
- 2 Spola in alluminio nichelato chimicamente
- 3 Guarnizioni in NBR

Component Parts and Materials

GB

- 1 Anodised and painted aluminium body
- 2 Chemical nickel-plated spool
- 3 NBR seals

Komponenten und Materialien

DE

- 1 Aluminiumgehäuse Eloxiert Und Lackiert
- 2 Schieber Aus Aluminium, Chemisch Vernickelt
- 3 Dichtungen Aus NBR

Matériaux et Composants

FR

- 1 Corps en aluminium anodisé et peint
- 2 Tiroir en aluminium, nickelé chimique
- 3 Joints en NBR

Materiales y Componentes

ES

- 1 Cuerpo en aluminio anodizado y barnizado
- 2 Corredora en aluminio niquelado químicamente
- 3 Juntas en NBR

Materiais e Componentes

PT

- 1 Corpo em alumínio anodizado e pintado
- 2 Carretel em alumínio niquelado quimicamente
- 3 Vedações em NBR





Tabella dei codici di ordinazione
Ordering codes
Bestellschlüssel
Code de commande
Tabla de codificación para pedidos
Tabela de codificação para compra

SERIE	Azionamento <i>Actuation Betätigung Actionnement Accionamiento Accionamento</i>	Riazionamento <i>Reactuation Rückstellung Rappel Reaccionamiento Retorno</i>	Vie <i>Ways Wege Voies Vias Vias</i>	Funzione <i>Function Funktion Fonction Función Funções</i>	Misura <i>Size Größe Dimension Medida Tamanho</i>
0 1 V	S	0	3	N C	0 2
	S = Solenoide <i>Solenoid Magnetspule Bobine Solenóide Solenóide</i>	0 = Monostabile con ritorno a molla <i>Monostable spring return Monostabil mit Federrückstellung Monostable à rappel par ressort Monoestable con retorno muelle Monoestável com retorno por mola</i> 1 = Bistabile <i>Bistable Bistabil Bistable Biestable Biestável</i> Su richiesta - If required - Auf Anfrage Sur demande - Bajo demanda - Sob encomenda 4 = Ritorno pneumatico <i>Pneumatic return Pneumatische Rückhubsperr Retour pneumatique Retorno neumático Retorno pneumático</i>	3 = 3/2 5 = 5/2 7 = 5/3	NO = Normalmente aperta <i>Normally open Normalerweise offen Normalement ouvert Normalmente abierta Normalmente aberta</i> NC = Normalmente chiusa <i>Normally closed Normalerweise geschlossen Normalement fermé Normalmente cerrada Normalmente fechada</i> CC = Centri chiusi <i>Normally closed Mittelstellung geschlossen Centre fermé Centros cerrados Centro fechado</i> OC = Centri aperti <i>Normally exhausted Mittelstellung offen Centre ouvert Centros abiertos Centro-aberto negativo</i> PC = Centri in pressione <i>Normally pressurized Mittelstellung unter Druck Centre sous pression Centros en presión Centro abierto positivo</i> 00 = Funzione non contemplata <i>Function not provided Funktion steht nicht zur Verfügung Fonction non disponible Función no contemplada Função não contemplada</i>	02 = 1/8 03 = 1/4 05 = 1/2

3/2 Vie - Ways - Wege - Voies - Vías - Vias

MONOSTABILE

MONOSTABLE
MONOSTABIL
MONOSTABLE
MONOESTABLE
MONOESTÁVEL




New

NC

NO

NC

Codice Code Nummer Code Código Código	Vie Ways Wege Voies Vías Vias	Funzione Function Funktion Fonction Función Funções	Misura Size Größe Dimension Medida Tamanho	Pack.
01V S0 3 NC 02	3/2	NC	1/8	1
01V S0 3 NC 03	3/2	NC	1/4	1
01V S0 3 NC 05	3/2	NC	1/2	1
01V S0 3 NO 02	3/2	NO	1/8	1
01V S0 3 NO 03	3/2	NO	1/4	1
01V S0 3 NO 05	3/2	NO	1/2	1

Codice Code Nummer Code Código Código	Vie Ways Wege Voies Vías Vias	Funzione Function Funktion Fonction Función Funções	Misura Size Größe Dimension Medida Tamanho	Pack.
01V S4 3 NC 02	3/2	NC	1/8	1
01V S4 3 NC 03	3/2	NC	1/4	1

Ritorno pneumatico - Pneumatic return - Pneumatische Rückhubsperre - Retour pneumatique - Retorno neumático - Retorno neumático

Monostabile con ritorno a molla - Monostable spring return - Monostabil mit Federückstellung - Monostable à rappel par ressort - Monoestable con retorno muelle - Monoestável com retorno por mola

01V S0 3 NC 02 01V S0 3 NO 02 01V S4 3 NC 02
01V S0 3 NC 05 01V S0 3 NO 05

01V S0 3 NC 03 01V S0 3 NO 03 01V S4 3 NC 03


3/2 Vie - Ways - Wege - Voies - Vías - Vias

BISTABILE


TWO STABLE POSITIONS

BISTABIL

BISTABLE


BIESTABLE

BIESTÁVEL




Codice Code Nummer Code Código Código	Vie Ways Wege Voies Vías Vias	Misura Size Größe Dimension Medida Tamanho	Pack.
01V S1 3 00 02	3/2	1/8	1
01V S1 3 00 03	3/2	1/4	1
01V S1 3 00 05	3/2	1/2	1


01V S1 3 00 02



01V S1 3 00 05



01V S1 3 00 03



5/2 Vie - Ways - Wege - Voies - Vías - Vias

MONOSTABILE

MONOSTABLE

MONOSTABIL



MONOSTABLE

MONOESTABLE

MONOESTÁVEL



New




Codice Code Nummer Code Código Código	Vie Ways Wege Voies Vias Vias	Misura Size Größe Dimension Medida Tamanho	Pack.
01V S0 5 00 02	5/2	1/8	1
01V S0 5 00 03	5/2	1/4	1
01V S0 5 00 05	5/2	1/2	1

Monostabile con ritorno a molla - Monostable spring return - Monostabil mit Federrückstellung - Monostable à rappel par ressort - Monoestable con retorno muelle - Monoestável com retorno por mola


Codice Code Nummer Code Código Código	Vie Ways Wege Voies Vias Vias	Misura Size Größe Dimension Medida Tamanho	Pack.
01V S4 5 00 02	5/2	1/8	1
01V S4 5 00 03	5/2	1/4	1

Ritorno pneumatico - Pneumatic return - Pneumatische Rückhubsperr - Retour pneumatique - Retorno neumático - Retorno pneumático


01V S0 5 00 02 01V S4 5 00 02



01V S0 5 00 05



01V S0 5 00 03 01V S4 5 00 03



5/2 Vie - Ways - Wege - Voies - Vías - Vias

BISTABILE


TWO STABLE POSITIONS

BISTABIL

BISTABLE


BIESTABLE

BIESTÁVEL




Codice Code Nummer Code Código Código	Vie Ways Wege Voies Vías Vias	Misura Size Größe Dimension Medida Tamanho	Pack.
01V S1 5 00 02	5/2	1/8	1
01V S1 5 00 03	5/2	1/4	1
01V S1 5 00 05	5/2	1/2	1


01V S1 5 00 02



01V S1 5 00 05



01V S1 5 00 03



5/3 Vie - Ways - Wege - Voies - Vías - Vias

MONOSTABILE CON RITORNO A MOLLA

MONOSTABLE SPRING RETURN

MONOSTABIL MIT FEDERRÜCKSTELLUNG


MONOSTABLE À RAPPEL PAR RESSORT

MONOESTABLE CON RETORNO POR MUELLE


MONOESTÁVEL COM RETORNO POR MOLA




Codice Code Nummer Code Código Código	Vie Ways Wege Voies Vías Vias	Funzione Function Funktion Fonction Función Funções	Misura Size Größe Dimension Medida Tamanho	Pack.
01V S0 7 CC 02	5/3	CC	1/8	1
01V S0 7 CC 03	5/3	CC	1/4	1
01V S0 7 CC 05	5/3	CC	1/2	1
01V S0 7 OC 02	5/3	OC	1/8	1
01V S0 7 OC 03	5/3	OC	1/4	1
01V S0 7 OC 05	5/3	OC	1/2	1
01V S0 7 PC 02	5/3	PC	1/8	1
01V S0 7 PC 03	5/3	PC	1/4	1
01V S0 7 PC 05	5/3	PC	1/2	1



CC




OC




PC

01V S0 7 CC 02 01V S0 7 OC 02 01V S0 7 PC 02



01V S0 7 CC 05 01V S0 7 OC 05 01V S0 7 PC 05



01V S0 7 CC 03 01V S0 7 OC 03 01V S0 7 PC 03

