

Hose Reel ALBA STAR Series II

For a Regular Demanding Daily Use and Need of Long Length Hose in the Professional Sector, i.e. in Plant Nurseries, Parks, Sports Grounds, Swimming Pools, Industrial Units, Workshops



Also in
Stainless Steel
ALBA STAR INOX
Series II


- Robust whole metal construction, UV resistant and environmentally friendly galvanized (zinc plated free of chrome VI)
- Hose friendly drum - no kinking
- High water flow capacity 3/4" (resistant)
- Wide, solid rubber wheels
- Hose reel - double bearing
- Without hose, pre-assembled in carton box
- Additional slip resistant stoppers on trolley frame
- Swivelling connector with ball bearing: simple reeling and unrolling
- Comfortable level of transportation: long and practical handle, easy to roll
- Highest tilt firmness

Materials:

- Hose reel: Steel galvanized zinc-plated (free of chrome VI)
- Wheels: solid rubber
- Swivelling connector: Brass MS 58 nickel-plated, ball bearing mounted

Max. Working Pressure	Temperature	Max. Hose Length	Media	
25 bar	up to + 100°C	1/2" (13 mm) = 120 m, 5/8" (16 mm) = 100 m, 3/4" (19 mm) = 80 m, 1" (25 mm) = 50 m	Water	1

Thread Connection	Version	Weight	Type No.
G 3/4 m	Hose i.D. 13 - Hose i.D. 16 - Hose i.D. 19 - Hose i.D. 25	14 kg	ALBA STAR 2



Ⓐ Total height:	1021 mm	Ⓔ Reel inside:	226 mm
Ⓑ Total length:	605 mm	Ⓕ Reel wheel:	555 mm
Ⓒ Total width:	603 mm	Ⓖ Wheel-Ø:	200 mm
Ⓓ Reel width:	296 mm	Ⓗ Wheel width:	46 mm

Hose Reel ALBA STAR INOX Series II

For the Food Industry: Ideal for Cheese Dairies, Creameries, Butcheries, Bakeries, Medical Laboratories, Swimming Pools etc.




- Totally made of electropolished stainless steel
- Hose friendly drum - no kinking
- High water flow capacity 3/4" (resistant)
- Wide, solid rubber wheels (abrasion-proof)
- Hose reel - double bearing
- Swivelling connector with ball bearing: simple reeling and unrolling
- Comfortable level of transportation: long and practical handle, easy to roll
- Highest tilt firmness
- Additional slip resistant stoppers on trolley frame
- Without hose, pre-assembled in carton box

Materials:

- Hose reel: Stainless steel electropolished
- Wheels: Solid rubber
- Swivelling connector: Brass Cuphin

Max. Working Pressure	Temperature	Max. Hose Length	Media	
25 bar	up to + 100°C	1/2" (13 mm) = 120 m, 5/8" (16 mm) = 100 m, 3/4" (19 mm) = 80 m, 1" (25 mm) = 50 m	Water	1

Thread Connection	Version	Weight	Type No.
G 3/4 m	Hose i.D. 13 - Hose i.D. 16 - Hose i.D. 19 - Hose i.D. 25	14 kg	ALBA STAR IN2



Ⓐ Total height:	1030 mm	Ⓔ Reel inside:	229 mm
Ⓑ Total length:	609,5 mm	Ⓕ Reel wheel:	555 mm
Ⓒ Total width:	608 mm	Ⓖ Wheel-Ø:	200 mm
Ⓓ Reel width:	296 mm	Ⓗ Wheel width:	46 mm

