




**Air Boy**® **Stainless** Ideal for fluids and aggressive environments

Blowgun with bent pipe, ø8mm stainless (AISI316)

The JWL ergonomic design is a classic in itself. We use the compressed air to ease the activation of the handle making it easy, precise and simple to operate.

The Air Boy® Stainless is produced in an impact-resistant acetal plastic (POM)





The durability of our blowguns is top notch - even after 28 million operations. Therefore, we are also proud to offer you a 25 year warranty on the valve system in your Air Boy® blowgun!

Materials		Specifications			Directives			
Handle and trigger	Acetal plastic	<b>P</b>	Max 16 bar			2003/10/CE	Max 85 dB	Ol
Valve	Acetal plastic		380 l/min (8 bar)			OSHA 1910.95 (b)	Max 90 dB 8 hr	Ol
Gaskets / O-rings	Nitrile		85 dB (8 bar), 84 dB (6 bar	r)		OSHA STD 1-13.1	Max 30 psi when blocked	-
Blowing tube & shaft	Stainless (AISI316)		-10°C to +80°C					
Spring	Stainless (AISI316)		~0,105 kg					
Flow	l/min(cfm) / bar(psi)	Noi	se level	dB / bar(psi)	Blo	owing force	Newton (g) / ba	ır(psi
600 (21,19) 500 (17,66) 400 (14,13)	380		Measured at a distance of Into the side of the nozzle	85		Measured on a 400 x 400mm from th (408)	e nozzle	,92

60 50



200

100