


MERKEL DOUBLE WIPER P 8



PRODUCT DESCRIPTION

Elastomer double wiper.

PRODUCT ADVANTAGES

The Merkel Double Wiper P 8 exerts inwards the wiping function of a U-ring, and a wiping action outwards against soiling.

- Strong wiping action against dirt
- Very good sealing effect against residual film of oil on the extending rod
- Wear-resistant

APPLICATION

- Industrial vehicles
- Presses
- Injection moulding machines

MATERIAL

<200 mm

Material	Code	Hardness
Nitrile rubber NBR	90 NBR 109	90 Shore A

>200 mm

Material	Code	Hardness
Nitrile rubber NBR	85 NBR B247	85 Shore A

OPERATING CONDITIONS

Running speed v	1 m/s
-----------------	-------

Medium/ Temperature	85 NBR B247	90 NBR 109
Hydraulic oils HL, HLP	-30 °C ... +100 °C	-30 °C ... +100 °C
HFA fluids	+5 °C ... +60 °C	+5 °C ... +60 °C
HFB fluids	+5 °C ... +60 °C	+5 °C ... +60 °C
HFC fluids	-30 °C ... +60 °C	-30 °C ... +60 °C
HFD fluids	–	–
Water	+5 °C ... +100 °C	+5 °C ... +90 °C
HETG (rapeseed oil)	-30 °C ... +80 °C	-30 °C ... +80 °C
HEES (synthetic ester)	-30 °C ... +80 °C	–
HEPG (glycol)	-30 °C ... +60 °C	-30 °C ... +60 °C
Mineral greases	-30 °C ... +100 °C	-30 °C ... +100 °C

DESIGN NOTES

Please observe our general design notes in → Technical Manual.

Surface quality

Peak-to-valley heights	R _a	R _{max}
Sliding surface	* μm	* μm
Groove base	≤1,6 μm	≤6,3 μm
Groove flanks	≤3,0 μm	≤15,0 μm

* Surface roughness of the sliding surface to suit the sealing component used.

Tolerances

Nominal Ø d	D	D ₁	D ₂
16 ... 1000 mm	H10		

The tolerance for the Ø d is defined by the buffer seal.

FITTING & INSTALLATION

Careful fitting is a prerequisite for the correct function of the Merkel Double Wiper P 8. Generally, wipers can be quickly and easily fitted by deforming into a kidney shape. → Technical Manual.

Lead-in chamfers

Length and angle are to be designed to suit the rod seal used.